



Electrical Safety

The machine will only operate on one voltage: it will be 110v or 230v. 110v machines will have a yellow industrial plug fitted. 230v machines will have either a normal square pin plug fitted, or a blue industrial plug. Read the following instructions for the machine.

110 VOLT HEATERS (YELLOW PLUG)

1. If a portable transformer is being used, plug the transformer directly into the 230 volt socket. DO not use any 230v extension cables.
2. If an extension cable is required, follow any special instructions given by the hire company. If the hire company have not given any special instructions, only a suitably rated heavy duty 110v extension cable, not longer than 50 metres (160 feet) should be used. The extension cable must only be used between the transformer and the machine.
3. Lay the extension cable out carefully avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. It must be unrolled fully or it will overheat and could catch fire.
4. Extension cable connections should be dry and safe.



230 VOLT MACHINES (SQUARE PIN OR BLUE PLUG)

1. A residual current device (rcd) must be used and plugged directly into the 230v socket. The machine must be plugged into the rcd. This will help to protect against electric shock if the cable or machine gets damaged.
2. Use the "TEST" button to check that the rcd is working each time it is used. Reset the rcd according to the instructions supplied with it.
3. If an extension cable is needed, follow any special instructions given by the hire company. If the hire company have not given any special instructions only a suitably rated heavy duty cable, not longer than 50 metres (160 feet) should be used. It should be plugged directly into the rcd.
4. Lay the extension cable out carefully avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. It should be fully unrolled or it will overheat and could catch fire.
5. Extension cable connections should be dry and safe.



Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhll B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

Paddle Mixer

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet

BEFORE you use the Paddle Mixer

1. Wear protective equipment including boots and goggles.
2. Some paddle mixers are mounted on wheelbarrow type frames to facilitate transporting the mix to point of use. Unplug the power supply before doing this.
3. If the paddle mixer is not constructed to transport a full container of mix do not attempt to do so.
4. Do not move any mixer, full or empty, until it is switched off and the power cable is disconnected.
5. If it is suspected that the cable may have been cut or damaged in any way, the paddle mixer should be switched off and unplugged at the mains before it is inspected. If the cable attached to the paddle mixer is damaged, stop using the machine. Contact the hire company. If an extension cable has been damaged do not use it again.
6. Care must be taken not to accidentally pull the plug from the socket.
7. Before leaving the paddle mixer unattended it must be switched off and the plug removed from the socket.
8. The operator is responsible for the security of the machine at all times during the hire. Theft or vandalism must be prevented by storing this equipment safely and securely.
9. If the equipment does not work properly do not attempt to repair it. Contact the hire company.
10. This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
11. This paddle mixer is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhll B37 7YE



1. Depending upon the machine the paddles may be made of metal, rubber, plastic or a combination of materials.
 2. The paddles may not be as durable as those found in conventional mixers, they must not be misused.
 3. Paddles must not be altered or removed, except for machines that are supplied with interchangeable paddles for different tasks.
 4. Wet cement mix is one substance among several that can cause contact dermatitis. Contact dermatitis is a rash that may occur when the skin reacts to certain substances.
- ### CEMENT MIXERS AND CONTACT DERMATITIS
1. The containers and paddles should be cleaned straight away unless another mix is being made immediately.
 2. If the mix hardens just a little it becomes much more difficult to clean.
 3. If the equipment is returned in a dirty condition a charge may be levied.
- ### PADDLES
1. Check on how the on/off switch operates - before switching the paddle mixer on it must be known how to stop it. Make sure that the mixer is switched off before plugging it into the supply.
 2. Paddles must not be altered or removed, except for machines that are supplied with interchangeable paddles for different tasks.
 3. Paddles must not be misused.
 4. Wet cement mix is one substance among several that can cause contact dermatitis. Contact dermatitis is a rash that may occur when the skin reacts to certain substances.
- ### CLEANING AND RETURNING THE EQUIPMENT
1. Mild dermatitis will heal providing there is no further contact. If the rash persists immediately and medical advice sought.
 2. The containers and paddles should be cleaned straight away unless another mix is being made immediately.
 3. If the equipment is returned in a dirty condition a charge may be levied.
 4. Wet cement mix is one substance among several that can cause contact dermatitis. Contact dermatitis is a rash that may occur when the skin reacts to certain substances.



WORK AREA

1. Do not use this paddle mixer where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.
2. Make sure that the area is clear and sage and that no-one is nearby or could cause a distraction.
3. The mixer should be set up on a firm flat surface, away from people, with enough space to keep the materials to be mixed, and near to where the mixed material will be used.
4. Other people should be protected from any danger and from dust. Warn others to keep away, barriers should be placed around the work area.
5. Operators
6. Most small paddle mixers only produce noise levels up to 65/70 dB(A) - which does not require hearing protection. If in doubt consult the hire company; if working in a noisy environment ear defenders may be needed.
7. Site regulations may require a safety helmet to be worn.
8. Anybody who is working nearby will also need to wear appropriate personal protective equipment.

1. Check the machine, container and paddles, cable, plug and all other equipment. If anything is found to be damaged, do not use the paddle mixer. Contact the hire company.
2. Check that the plug on the machine matches the available supply.
3. Connections should not be forced or improvised.
4. Machines with a cylindrical yellow industrial plug are designed to run off a special 110v supply. The hire company will have provided a portable transformer if the machine is to be powered from a normal mains 230v supply. If a portable transformer has been supplied, operators must take care not to injure

PADDLE MIXER

1. Check the machine, container and paddles, cable, plug and all other equipment. If anything is found to be damaged, do not use the paddle mixer. Contact the hire company.
2. Check that the plug on the machine matches the available supply.
3. Connections should not be forced or improvised.
4. Machines with a cylindrical yellow industrial plug are designed to run off a special 110v supply. The hire company will have provided a portable transformer if the machine is to be powered from a normal mains 230v supply. If a portable transformer has been supplied, operators must take care not to injure