



Using the Auger

1. Wear the protective equipment including boots and gloves.
2. Plan working positions and the route to be taken around the holes to be dug. Avoid ground where there is building debris such as bricks, wire or timber offcuts.
3. Once the auger has been started, it can be lifted it into position. Operators must check that they have a secure grip and footing before starting work.
4. Always hold the machine securely with both hands on the handgrips and be prepared for any unexpected increase in turning force if the auger meets an obstruction.
5. As soon as the guide tip of the auger has broken the soil surface, use full throttle to continue drilling.
6. Stay alert and always be ready to stop the engine straightaway if the auger starts to jam. If the Auger isn't stopped, the body of the machine will spin around and control will be lost.
7. If the machine starts to labour and slow down do not force it so hard. Lift the machine with the auger turning to allow soil, clay and stones to be freed from the hole. Steady drilling keeping the auger speed up is more effective than aggressive pressure.
8. Extensions should be added only when the auger has penetrated into the ground as far as it can.
9. Release the auger and lift the machine clear. Locate an extension onto the auger spindle and lock it into place. Now locate the borer on to the top of the extension and lock it into place.
10. If the auger appears to be starting to become blunt, do not force the machine. Contact the hire company to reset the cutting edge.
11. If the auger jams, stop the engine straightaway. Set the gear lock and turn the entire machine anti-clockwise to screw the auger out of the ground. Disengage the gear lock as soon as the auger is free.
12. When moving on to the next hole, carry the machine carefully, with the engine idling.
13. Take care not to trip on the soil from the recently dug hole or other obstacles.
14. Watch out for signs that vibration from the work may be affecting your hands. If fingers start to tingle or feel numb, take a short break from cutting work. Exercise the fingers to encourage blood circulation.
15. To help prevent vibration affecting hands, operate the machine for shorter periods. Keep hands warm – wearing gloves may help do this.
16. If someone approaches, stop work and let the machine idle until they are clear.
17. Stop the engine to make any adjustments or clear debris tangled in the auger.
18. Stop the engine if leaving the machine unattended.
19. If the auger does not work properly do not attempt to repair it. Contact the hire company.

Please keep this leaflet safely as it may be required for future reference



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read this entire leaflet BEFORE using the 1 Man Post Hole Auger

1. Petrol mixture is highly flammable. Take care not to cause a fire or explosion.
2. This auger is designed to drill holes in soil or clay using the appropriate attachments. Do not use it for anything else. Carelessness or misuse could cause a serious or fatal accident.
3. Make sure that there are no hidden electricity cables, gas or water pipes, or other obstructions where drilling is going to take place.
4. Plan the work and think ahead to make sure that the work will always be carried out safely.
5. The following items of personal protective equipment must be worn as a minimum: ear muffs or plugs giving protection for levels up to 107 dB(A); safety boots; gloves.
6. This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
7. This machine is designed for operation by two able bodied adults. Anyone with either temporary or permanent disability must seek expert advice before using it.

WORK AREA

1. Do not use this machine where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.
2. Using this equipment indoors or in confined spaces could cause **fatal** carbon monoxide poisoning. **Never** use it in domestic premises and only use it in other indoor situations if its suitability and the ventilation required has been **fully** assessed. Mechanical extraction ventilation will almost always be required
3. Make sure the area is clear and safe and that no-one is nearby who could cause a distraction.
4. Warn other people to keep away from the working area: put up warning signs or barriers.

(Continued overleaf...)



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

with the engine controls and throttle lever on top. Make sure that the auger is only resting lightly on the ground and is free to turn.

3. Check that the gear lock is off.
4. Move the control lever to the start position.
5. If the engine is warm, check that the choke control is in the open position. If the engine has not yet closed position. Only set the choke lever to the closed position if the engine has a decompression valve, set it. It needs to be set each time a fresh attempt is made to start the engine.
7. Move the throttle lever to about half throttle position and use the interlock to hold it open.
8. Hold the machine down firmly with the left hand. Do not stand or kneel on the handles or engine housing.
9. Be prepared for the auger turning when the engine starts.
10. With the right hand, pullout the starter handle slowly until you can feel that the starter has engaged with the engine. Don't pull it too far, or it may break.
11. Guide the cord back so that it recoils correctly.
12. If the engine is now running, briefly open the throttle – it will revert to its normal position and the engine will idle. Set the choke control to the open position.
13. If the engine did not start, set the choke control to the open position, set any decompression valve, and pull the starter cord again.
14. In cold weather, it may be necessary to let the engine warm up by gently opening the throttle, before starting work.

1. This section describes the controls found on this section of the auger.

1. The throttle lever is on the handlebar, hand. There is also a part-throttle interlock, which will hold the throttle partly open for starting. This may be on the motor housing, or by the throttle lever.
3. The main control lever has two positions. Under normal running, it is at the position marked START or RUN. Push the control lever forward to the position marked STOP to stop the auger.
4. The machine may have a decompression valve. This is only used when starting the auger – it needs to be pressed before each fresh attempt to start the engine.
5. The choke control should only be used when first attempting to start an engine from cold.
6. There will be a gear lock on the gearbox. Only use this when freeing a jammed auger. At all other times it should be unlocked.
1. This section describes the starting procedure for most augers. If the hire company has given special instructions, follow them. Otherwise, follow the instructions given below.
2. Lay the machine on the ground, resting on the handles and the tip of the auger.



Before Starting Work...

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solithull B37 7YE



1. The following items of personal protective equipment (ppe) are the minimum which should be worn when using this machine. Particular jobs or environments may require a higher level of protection.

2. This equipment is likely to cause noise levels up to 107 dB(A) - wear appropriate ear muffs or plugs giving hearing protection for this level.
3. Gloves should be worn to protect hands while working with the machine, especially when handling the auger.
4. Safety boots must be worn when working with this machine.
5. Make sure that there is no loose or flapping clothing could get caught in the auger.
6. Anyone who is working nearby will also need to wear appropriate personal protective equipment.
7. Vibration from working with this machine for long periods can be hazardous. Warm hands up before starting work, and wear gloves to keep hands warm while working.
1. Check the machine, including the fuel tank, handles, and auger. If anything is found to be damaged, do not use the auger - contact the hire company.
2. Fit the appropriate auger for the holes to be drilled. Only use the correct augers as supplied by the hire company.

POST HOLE AUGER

1. No smoking.

2. Use a fresh mixture of two stroke engine oil with petrol. If the hire company have given special instructions on how much oil to use, follow them. Otherwise, use 1 measure of two stroke oil to 25 measures of petrol (40 ml per litre).
3. Stop the engine and let it cool down.
4. If possible move the machine away from the work area.
5. Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.
6. Shake the fuel can to mix the petrol and oil.
7. Use a funnel when refuelling. Do not spill any fuel on people or the machine.
8. Wipe any fuel off the machine. Dispose of fuel soaked cloth carefully.
9. If any fuel is spilled on the ground, wipe it up or cover it with soil.
10. If any fuel is spilled on clothes, change them straight away.
11. Put all fuel caps back on properly, and move the fuel can to a safe, cool place.

REFUELLING

