

Slide Compound Saw

LS1018L

1 430 W • 260 mm • 4 300 min⁻¹

Efficient and accurate saw with a laser for high-capacity applications

An accurate high-capacity saw with a 1 430 W motor for building and other worksites. The dual slide system reduces the need for space, enabling the machine to be placed by a wall. The bevel lock is located at the front of the saw. Excellent dust removal function.



Technical specifications

Capacity 90°	91x310 mm
Continuous Input Power	1430 W
No load speed	4300 min ⁻¹
Capacity 45°	91 x 220 mm
Max. Bevel Range (Left)	45 / 45 °
Max. Mitre Range (Left)	47 / 60 °
Blade Diameter	255 / 260 mm
Bore Size (Arbor Diameter)	30 mm
Power Supply Cord	2,5 m
Sound Power Level (L _{WA})	102 dB(A)
Sound Pressure Level (L _{pA})	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Laser Class	2M
Weight Without Cable (EPTA)	19,9 kg

User benefits

- Large cutting capacity in a compact design and less weight
- Less weight and compact design for job site portability
- Soft start feature for smooth start-ups
- Ergonomic rubberised D-handle design for better fit and added comfort
- Large precision machined aluminium base supports material for more efficient cutting
- Electric brake for maximum productivity
- Dust bag for a cleaner work environment
- See-through blade guard system for greater visibility of blade and line of cut
- Oversized trigger switch for better fit, added comfort and easier operation

EAN 0088381608268

Link to product - www.makita.uk.com



Related products

Optional AC

122930-6

Horizontal Vice Assembly



762001-3

Triangular Rule



B-29496

Circular saw blade, Specialized T.C.T,



B-64630

Circular Saw Blade, Efficut, TCT,



JM00000382

Saw Blade 260x2.3mm for LS1018L

JM23100501

Dust bag



JM23100502

Vertical Vice assembly



JM23200110

SUB FENCE COMP R LS1018L



Other

User manual

Parts drawing