

Demolition Hammer

HM0871C

1 100 W • SDS-MAX • 8.1 J

Efficient demolition hammer with anti-vibration system

An efficient demolition hammer. Compatible with SDS-MAX bits. Motor capacity of 1,100W and impact energy of 7.6J provide efficient material removal. Adjustable impact rate: 1,100-2,650 min⁻¹. AVT technology for low vibration.



AVT **SOFT**
ANTI VIBRATION TECHNOLOGY NO LOAD

Technical specifications

Continuous Input Power 240V	1100 W
Impacts per Minute (IPM)	1100 - 2650 min ⁻¹
Impact Energy	8,1 J
Power Supply Cord	4,0 m
Sound Power Level (L _{WA})	93 dB(A)
Sound Pressure Level (L _{pA})	85 dB(A)
Noise Uncertainty (K Factor)	2,3 dB(A)
Vibration Level, Chiselling	11,4 m/s ²
Vibration Uncertainty (K Factor), Chiselling	1,5 m/s ²
Vibration Level, Chiselling with D-type Side Handle	12,8 m/s ²
Vibration Uncertainty (K Factor), Chiselling with D-type Side Handle	1,5 m/s ²
Weight Without Cable	5,6 kg
Product Dimensions (L x W x H):	466 x 116 x 230 mm

User benefits

- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- The service light indicates the need for carbon brush replacement and malfunctions in the switch and connection cable
- LED light illuminates the work site
- Easy-to-operate slide switch increases productivity and allows for continuous use
- Variable speed control dial enables user to match the speed to the application for greater versatility
- 12 bit angle settings allow the bit to be set at different positions for operating convenience
- Soft start suppresses start-up reaction for more control and better accuracy
- One touch sliding chuck enables quick and easy bit changes
- Constant speed control maintains constant speed under load

EAN 0088381605335

Link to product - www.makitauk.com



Related products

Optional AC

135332-7

Grip 36 Assembly



194683-7

Grease vessel set, 100 ml



198993-4

Grease vessel for bit 100 ml



199144-2

Dust Extraction Attachment



Other

User manual

Parts drawing